



AS ACOUSTIC

SYSTEM NEVER FAIL

8AS300

Nominal Impedance - 8
Minimum Impedance - 7.2
Nominal Power - 300 W
Continuous Power - 500 W
Sensitivity - 98 dB
Freq Range- 90 Hz - 5000 Hz
Voice Coil - 51 mm (2 in)



10AS700

Nominal Impedance - 8
Minimum Impedance - 7.2
Nominal Power - 700 W
Continuous Power - 1000 W
Sensitivity - 100dB
Freq Range- 60 Hz - 5000 Hz
Voice Coil - 76 mm (3 in)

12AS1000

Nominal Impedance - 8
Minimum Impedance - 7.2
Nominal Power - 1000 W
Continuous Power - 1200 W
Sensitivity - 99dB
Freq Range- 60 Hz - 5000 Hz
Voice Coil - 76 mm (3 in)



21SW3000

Nominal Impedance - 8
Minimum Impedance - 7.2
Nominal Power - 3000 W
Continuous Power - 3500 W
Sensitivity - 99 dB
Freq Range- 25 Hz - 5000 Hz
Voice Coil - 139.7 mm (5.5in)



AS ACOUSTIC

SYSTEM NEVER FAIL

8AS300

Nominal Impedance - 8
Minimum Impedance -7.2
Nominal Power - 300 W
Continuous Power - 500 W
Sensitivity - 98 dB
Freq Range- 90 Hz - 5000 Hz
Voice Coil - 51 mm (2 in)



10AS700

Nominal Impedance - 8
Minimum Impedance -7.2
Nominal Power - 700 W
Continuous Power - 1000 W
Sensitivity - 100dB
Freq Range- 60 Hz - 5000 Hz
Voice Coil - 76 mm (3 in)

12AS1000

Nominal Impedance - 8
Minimum Impedance -7.2
Nominal Power - 1000 W
Continuous Power - 1200 W
Sensitivity - 99dB
Freq Range- 60 Hz - 5000 Hz
Voice Coil - 76 mm (3 in)



21SW3000

Nominal Impedance - 8
Minimum Impedance -7.2
Nominal Power - 3000 W
Continuous Power - 3500 W
Sensitivity - 99 dB
Freq Range- 25 Hz - 5000 Hz
Voice Coil - 139.7 mm (5.5in)